

Geographic Coordinate Data Base

Coverage Format

Description Document

Department of the Interior
Bureau of Land Management
Building 40, Denver Federal Center
Denver, Colorado 80225-0047

April 2000

Document prepared by
NexGen Technologies, Inc.
11990 Grant Street, Suite 214
Northglenn, CO 80233

Contract No. NBC 990001
Task Order 0003

**GCDB Coverage Format
Description Document**



TABLE OF CONTENTS

1.0	Introduction	1
2.0	GCDB Township Coverages	2
2.1	Definitions of Table Headings, Table Suffixes and Item Types	4
2.2	Coverage Tables	5
2.3	Coverage Table Examples	15
3.0	Translation to Cadastral Data Transfer Profile for the National Spatial Data Infrastructure	19

GCDB Coverage Format Description Document



1.0 Introduction

The GCDB Data Prep project combines automated and manual processes to create ARC/INFO coverages from raw survey information collected and maintained by the Bureau of Land Management. In accordance with the ARC/INFO georelational model, spatial features such as control points, survey lines and ownership areas are maintained as records in database tables. Unique identifiers, maintained by ARC/INFO, provide the link between the spatial information that locates the feature and attribute information that describes the feature. The purpose of this document is to describe the database tables and attributes created by the GCDB Data Prep project.

The GCDB Coverage Format Guide is presented in three (3) sections.

- Section 1 Introduction describes the document.
- Section 2 GCDB Township Coverages defines the tabular structures for the created ARC/INFO coverages.
- Section 3 Translation to the Cadastral Data Transfer Profile provides a cross-walk between the attribute items making up the Cadastral Data Content Standard and the items created by the GCDB Data Prep processes.

GCDB Coverage Format Description Document



2.0 GCDB Township Coverages

2.0.1 Why Three Coverages Are Needed For The GCDB Download Site

The GCDB input text files contain survey lines and points that describe survey types and land descriptions for areas within a township, including Principal Meridian, State, Township and Range, and Sections. Incorporation of GCDB points into a GIS format is dependent upon the geo-relational model used by Arc/INFO. The geo-relational model enforces a single label point within any one polygon. As a result, areas that have multiple label points will not be represented in the GCDB Coverage.

The Control Points and Label Points coverages are included with the GCDB coverage to ensure all data is completely represented. The Control coverage contains only those points that are used as control points. The Label Points coverage contains a complete graphical representation of the GCDB files including all label points and survey lines. The GCDB coverage contains the region features (township, section, and quarter) with a single label point connected to land description attributes that relate specifically to that point.

2.0.2 GCDB Township Coverages

Township coverages are stored in sub-directories under the \$GCDB_COVERAGES directory. The township directory name is constructed from the 2 letter state code, 2 digit principal meridian code, and tier/range codes (for example: nm23t0320n0050w for Township 32N Range 5W first duplicate of the NM Principal Meridian). The following coverages are created by the GCDB Data Prep processes;

<u>Name</u>	<u>Spatial Features</u>	<u>ARC/INFO Feature Class</u>
CTRL	Control Points	Points
LABELS_GCDB	Area points, Survey lines	Points, Arcs, and Nodes
GCDB	Land areas, Survey lines	Polygons, Regions, Arcs, Nodes, and Labels

2.0.3 Control Points Coverage

The CTRL coverage is created from GCDB input files (e.g., *township.con*) stored under the \$GCDB_CONV_IN township directory. The CTRL coverage is a point coverage that contains control locations for the specified township. Control point features are described by elements such as a point identifier, elevation and reliability measurements. The control points are provided in a separate coverage for easy identification.

2.0.4 Label Points Coverage

The LABELS_GCDB coverage is created from GCDB input files containing point and line (e.g., *a*township (point), *l*township (lines)) stored under the \$GCDB_CONV_IN township

GCDB Coverage Format Description Document



directory. Each record in the GCDB input label (point) file is represented as a discrete point feature in the LABELS_GCDB coverage. Each record in the input survey line files, excluding duplicate lines (i.e., lines with the same end points), is represented by a discrete line feature in the LABELS_GCDB coverage. The LABELS_GCDB coverage contains label (point) and survey line features that provide land descriptions for a given area. The LABELS_GCDB coverage provides the basis for the GCDB coverage polygon and region topology.

2.0.5 GCDB Coverage

Label point features in the LABELS_GCDB coverage are overlaid with polygons in the GCDB coverage to support the aggregation of polygons into **Township**, **Section** and **Quarter** region features. The base polygons in the GCDB coverage have no inherent meaning of their own, rather they form the building blocks for the different region subclasses. The GCDB Coverage is a region coverage with the following three region subclasses;

- * **Township** - contains a single feature whose spatial extent is that of the township. Descriptive information includes the State, Principal Meridian and Township.
- * **Section** - contains features that represent the sections within the township. Each feature is described by the section number.
- * **Quarter** - contains features that represent quarter subdivisions of the sections. Features are attributed with a two-letter, directional code describing the quarter.

In addition to region features, the GCDB coverage also contains arcs that represent the survey lines used to define the areal features. Arcs are stored as two point segments and are described by such attributes as length and type. Locations, reliabilities and elevation for the arc endpoints are stored and maintained as node features in the GCDB coverage.

lq25n12w

2.0.6 GCDB Arc/INFO Export (Interchange) Files

After a Township file has been successfully converted, topo-checked, it's coverage edited and saved, the user selects "Export E00" button from the DCSS interface to convert the coverage to an Arc/INFO export or interchange file format. Arc/INFO export files are binary files that allow easy transfer of coverage data. Each of the three township coverages are converted to export files and typically have an "*.e00" extension (e.g., co06t0330s0630w_gcdb.e00, co06t0330s0630w_ctl.e00, and co06t0330s0630w_lbl.e00). During the download process from the GCDB Download site, the three export files are zipped together and delivered to the client machine.

GCDB Coverage Format Description Document



2.1 Definitions of Table Headings, Table Suffixes and Item Types

2.1.1 Table Headings

COL	Starting position within the record for the item that follows.
ITEM NAME	Name of the data field.
WIDTH	Internal storage width of the item.
OUTPUT	Output width of the item.
TYPE	Item type.
N.DEC	Number of decimal places.
A/I	Item generated by Arc/Info.

2.1.2 Table Suffixes

Spatial features are managed by ARC/INFO in database tables that associate coordinate data with attribute information. Listed below are the table name extensions that correspond to the features stored in the table. Standard items, those maintained by ARC/INFO are also listed. The italic references, *cover* and *subclass*, are generic references to the coverage and subclass name, respectively.

.PAT **Point** Attribute Table
Standard items: Area, Perimeter, *cover#*, *cover-id*

.PAT **Polygon** Attribute Table
Standard items: Area, Perimeter, *cover#*, *cover-id*

Note: Point features are simply polygon features with zero dimension (I.e. no area or perimeter). The area and perimeter fields are set to zero for point features, thus distinguishing them from polygon features.

.PAT<subclass> Region Subclass Attribute Table
Standard items: Area, Perimeter, *subclass#*, *subclass-id*

.AAT **Arc** Attribute Table
Standard Items: FNODE#, TNODE#, LPOLY#, RPOLY#, Length, *cover#*,
cover-id

.NAT Node Attribute Table
Standard Items: ARC#, *cover#*, *cover-id*

2.1.3 Item Types Used in GCDB Coverages

B(Binary)	1-4 byte integer item. No decimal positions allowed.
C(Character)	Character field.
F(Floating)	Number stored in floating-point format.
I(Integer)	1-16 byte integer item. No decimal positions are allowed.
N(Number)	Number with decimal places.

GCDB Coverage Format Description Document



2.2 Coverage Tables

2.2.1 CONTROL POINT ATTRIBUTES (ctrl.pat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Not used.
9	PERIMETER	8	18	F	5	Y	Not used.
17	CTRL#	4	5	B	-	Y	Internal control point ID.
21	CTRL-ID	4	5	B	-	Y	User control point ID.
25	ELEV	9	9	N	3	N	Elevation.in feet.
34	ERROR_N	4	4	I	-	N	Northing error in feet.(GMM). Average reliability (PCCS).
38	ERROR_E	5	5	I	-	N	Easting error in feet (GMM). Maximum reliability (PCCS).
42	POINT_ID	6	6	C	-	N	Control Point/Station ID.
48	X-COORD	14	14	N	9	N	Longitude in decimal degrees.
62	Y-COORD	14	14	N	9	N	Latitude in decimal degrees.
76	AVAIL_FLAG	1	1	C	-	N	Flag indicating that this control point is available, but was not actually used for control purposes (Y/N).

GCDB Coverage Format Description Document



2.2.2 LABEL ATTRIBUTES (labels_gcdb.pat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Not used.
9	PERIMETER	8	18	F	5	Y	Not used.
17	LABELS_GCDB#	4	5	B	-	Y	Internal label point ID.
21	LABELS_GCDB-ID	4	5	B	-	Y	User label point ID.
25	SEC_NO	3	3	C	-	N	Section number.
28	SEC_FRAC	1	1	C	-	N	Not used - Reserved for future use. Section fractional code. (Blank) = full section. 1 = 1/4 2 = 1/2 3 = 3/4
29	SEC_DUP	1	1	C	-	N	Not used - Reserved for future use. (Blank) = not duplicate A = First duplicate (second occurrence of same section number). B = Second duplicate (third occurrence of same section number).
30	NOMINAL_LOCATION	5	5	C	-	N	Nominal location (A-Q).
31	QUARTER	2	2	C	-	N	Quarter section (NE, NW, SE, SW).
33	SURVEY_TYPE	1	1	C	-	N	Survey type (A,B,C,D,E,G,H,I,J,K,L,M,N,O,P,Q, R,S,T,U,W,X,Y,Z).
34	SURVEY_NUMBER	5	5	C	-	N	Survey number.
39	SURVEY_SUFFIX	2	2	C	-	N	Survey suffix.
41	SURVEY_NOTE	3	3	C	-	N	Survey note.
44	ACREAGE	9	9	C	-	N	Acreage.
53	CONFLICT_CD	2	2	C	-	N	Conflict code. (Not used - reserved for future use).
55	PRINMER_CD	2	2	C	-	N	Principal meridian code.
57	TIER_NO	3	3	C	-	N	Tier number.

GCDB Coverage Format Description Document



60	TIER_FRAC	1	1	C	-	N	Tier fractional code 0 = Not a fractional tier. 1 = 1/4 Tier. 2 = 1/2 Tier. 3 = 3/4 Tier.
61	TIER_DIR_CD	1	1	C	-	N	Tier direction code (N,S).
62	RANGE_NO	3	3	C	-	N	Range number.
65	RANGE_FRAC	1	1	C	-	N	Range fractional code. 0 = Not a fractional range. 1 = 1/4 Range. 2 = 1 /2 Range. 3 = 3/4 Range.
66	RANGE_DIR_CD	1	1	C	-	N	Range direction code (E,W).
67	TOWNSHIP_DUP_CD	1	1	C	-	N	Township duplicate code. (Blank) = Not a duplicate township. A = First duplicate (second occurrence of same township). B = Second duplicate (third occurrence of same township).
68	LATITUDE	14	14	N	9	N	Latitude of label point in decimal degrees.
82	LONGITUDE	14	14	N	9	N	Longitude of label point in decimal degrees.

GCDB Coverage Format Description Document



2.2.3 NODE ATTRIBUTES (gcdb.nat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	ARC#	4	5	B	-	Y	Internal arc number corresponding to the node.
5	GCDB#	4	5	B	-	Y	Internal node ID.
9	GCDB-ID	4	5	B	-	Y	User node ID.
13	ELEV	9	9	N	2	N	Elevation.
22	ERROR_N	4	4	I	-	N	Northing error in feet.(GMM). Average reliability (PCCS).
26	ERROR_E	5	5	I	-	N	Easting error in feet (GMM). Maximum reliability (PCCS).
30	LINE_CNT	3	3	I	-	N	Line count.
33	LINE_TYPE	2	2	I	-	N	Line type (0 = Section/Township/Special survey line 1 = 20 chain line 2 = 40 chain line 3 = 60 chain line 4 = Blank line)
35	LINE_PEN	2	2	I	-	N	Pen command.
37	LX_SEC	1	1	I	-	N	Not used.
38	POINT_ID	6	6	C	-	N	Station/Point ID.
44	X-UTM-ST	11	11	N	2	N	X coordinate in UTM, State Plane, or map inches..
55	Y-UTM-ST	11	11	N	2	N	Y coordinate in UTM, State Plane, or map inches..
66	X-COORD	14	14	N	9	N	Longitude in decimal degrees.
80	Y-COORD	14	14	N	9	N	Latitude in decimal degrees.
94	SYM_VALUE	3	3	I	-	N	Symbol value for node.
	REDEFINED ITEMS						
38	PREFIX	3	3	C	-	N	Point ID prefix.
41	SUFFIX	3	3	C	-	N	Point ID suffix.

GCDB Coverage Format Description Document



2.2.4 ARC ATTRIBUTES (gcdb.aat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	FNODE#	4	5	B	-	Y	Internal number of the from-node.
5	TNODE#	4	5	B	-	Y	Internal number of the to-node
9	LPOLY#	4	5	B	-	Y	Left polygon number.
13	RPOLY#	4	5	B	-	Y	Right polygon number.
17	LENGTH	8	18	F	5	Y	Length of arc.
25	GCDB#	4	5	B	-	Y	Internal Arc ID.
29	GCDB-ID	4	5	B	-	Y	User Arc ID.
33	TYPE	6	6	I	-	N	Line type.
39	SYMBOL	6	6	I	-	N	Line symbol.
45	ORIG_ARC	4	5	B	-	N	Original arc flag.
49	DANGLE_FLAG	4	4	C	-	N	Dangle flag.

GCDB Coverage Format Description Document



2.2.5 ARC ATTRIBUTES (for tangent, circular, and spiral curves - gcdb.aat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	FNODE#	4	5	B	-	Y	Internal number of the from-node.
5	TNODE#	4	5	B	-	Y	Internal number of the to-node.
9	LPOLY#	4	5	B	-	Y	Left polygon number.
13	RPOLY#	4	5	B	-	Y	Right polygon number.
17	LENGTH	8	18	F	5	Y	Length of arc.
25	GCDB#	4	5	B	-	Y	Internal Arc ID.
29	GCDB-ID	4	5	B	-	Y	User Arc ID.
33	ANGLE	10	10	C	-	Y	The chord direction of circular curves and spirals.
43	DISTANCE	8	8	C	-	Y	The chord distance of circular curves and spirals.
51	RADIUS	8	8	C	-	Y	The circular curve radius or the first radius of a spiral.
59	DELTA	10	10	C	-	Y	The delta angle of a circular curve or spiral.
69	TANGENT	8	8	C	-	Y	The tangent length of a circular curve or the first tangent length of a spiral.
77	ARCLENGTH	8	8	C	-	Y	The arc length of a circular curve or spiral.
85	SIDE	1	1	C	-	Y	The side where the radius point (for curves) or radius points (for spirals) are located with respect to circular curve or spiral (to the right or to the left of the circular curve or spiral).
86	RADIUS2	8	8	C	-	Y	The second radius of a spiral. TANGENT2 is the second tangent length of a spiral.
94	TANGENT2	8	8	C	-	Y	The second tangent length of a spiral.
102	TYPE	6	6	I	-	N	Line type.
108	SYMBOL	6	6	I	-	N	Line symbol.
114	ORIG_ARC	4	5	B	-	N	Original arc flag.
118	DANGLE_FLAG	4	4	C	-	N	Dangle flag.

GCDB Coverage Format Description Document



2.2.6 POLYGON ATTRIBUTES (gcdb.pat)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Area of polygon.
9	PERIMETER	8	18	F	5	Y	Perimeter of polygon.
17	GCDB#	4	5	B	-	Y	Internal polygon ID.
21	GCDB-ID	4	5	B	-	Y	User polygon ID.
25	SEC_NO	3	3	C	-	N	Section number.
28	SEC_FRAC	1	1	C	-	N	Not used - Reserved for future use. Section fractional code. (Blank) = full section. 1 = 1/4 2 = 1/2 3 = 3/4
29	SEC_DUP	1	1	C	-	N	Not used - Reserved for future use. (Blank) = not duplicate A = First duplicate (second occurrence of same section number). B = Second duplicate (third occurrence of same section number).
30	NOMINAL_LOCATION	5	5	C	-	N	Nominal location (A-Q).
31	QUARTER	2	2	C	-	N	Quarter section (NE, NW, SE, SW).
33	SURVEY_TYPE	1	1	C	-	N	Survey type (A,B,C,D,E,G,H,I,J,K,L,M,N,O,P,Q, R,S,T,U,W,X,Y,Z)
34	SURVEY_NUMBER	5	5	C	-	N	Survey number.
39	SURVEY_SUFFIX	2	2	C	-	N	Survey suffix.
41	SURVEY_NOTE	3	3	C	-	N	Survey note.
44	ACREAGE	9	9	C	-	N	Acreage.
53	CONFLICT_CD	2	2	C	-	N	Conflict code .(Not used - reserved for future use).
55	PRINMER_CD	2	2	C	-	N	Principal meridian code.
57	TIER_NO	3	3	C	-	N	Tier number.

**GCDB Coverage Format
Description Document**



60	TIER_FRAC	1	1	C	-	N	Tier fractional code 0 = Not a fractional tier. 1 = 1/4 Tier. 2 = 1/2 Tier. 3 = 3/4 Tier.
61	TIER_DIR_CD	1	1	C	-	N	Tier direction code (N,S).
62	RANGE_NO	3	3	C	-	N	Range number.
65	RANGE_FRAC	1	1	C	-	N	Range fractional code. 0 = Not a fractional range. 1 = 1/4 Range. 2 = 1 /2 Range. 3 = 3/4 Range.
66	RANGE_DIR_CD	1	1	C	-	N	Range direction code (E,W).
67	TOWNSHIP_DUP_CD	1	1	C	-	N	Township duplicate code. (Blank) = Not a duplicate township. A = First duplicate (second occurrence of same township). B = Second duplicate (third occurrence of same township).
68	LATITUDE	14	14	N	9	N	Latitude of label point in decimal degrees.
82	LONGITUDE	14	14	N	9	N	Longitude of label point in decimal degrees.

GCDB Coverage Format Description Document



2.2.7 REGION ATTRIBUTES

SUBCLASS TWP (gcdb.pattwp)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Area of region.
9	PERIMETER	8	18	F	5	Y	Perimeter of region.
17	TWP#	4	5	B	-	Y	Internal region ID.
21	TWP-ID	4	5	B	-	Y	User region ID.
25	STATE_CD	2	2	C	-	N	Two letter state code.
27	PRINMER_CD	2	2	C	-	N	Principal meridian code.
29	TIER_NO	3	3	C	-	N	Tier number.
32	TIER_FRAC	1	1	C	-	N	Tier fractional code 0 = Not a fractional tier. 1 = 1/4 Tier. 2 = 1/2 Tier. 3 = 3/4 Tier.
33	TIER_DIR_CD	1	1	C	-	N	Tier direction code (N,S).
34	RANGE_NO	3	3	C	-	N	Range number.
37	RANGE_FRAC	1	1	C	-	N	Range fractional code. 0 = Not a fractional range. 1 = 1/4 Range. 2 = 1 /2 Range. 3 = 3/4 Range.
38	RANGE_DIR_CD	1	1	C	-	N	Range direction code (E,W).
39	TOWNSHIP_DUP_CD	1	1	C	-	N	Township duplicate code. (Blank) = Not a duplicate township. A = First duplicate (second occurrence of same township). B = Second duplicate (third occurrence of same township).
	REDEFINED ITEMS						
25	TOWNSHIP	15	15	C	-	N	State, Principal Meridian, Township and Range.

GCDB Coverage Format Description Document



SUBCLASS SECT (gcdb.patsect)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Area of region.
9	PERIMETER	8	18	F	5	Y	Perimeter of region.
17	SECT#	4	5	B	-	Y	Internal region ID.
21	SECT-ID	4	5	B	-	Y	User region ID.
25	SECTION	3	3	C	-	N	Section number.

SUBCLASS QTR (gcdb.patqtr)

COL	ITEM NAME	WIDTH	OUTPUT	TYPE	N.DEC	A/I	DESCRIPTION
1	AREA	8	18	F	5	Y	Area of region.
9	PERIMETER	8	18	F	5	Y	Perimeter of region.
17	QTR#	4	5	B	-	Y	Internal region ID.
21	QTR-ID	4	5	B	-	Y	User region ID.
25	QUARTER	2	2	C	-	N	Quarter (NE,NW,SW,SE).

GCDB Coverage Format Description Document



2.3 Coverage Table Examples

2.3.1 CTRL.PAT

```
AREA      =      0.00000
PERIMETER =      0.00000
CTRL#     =      9
CTRL-ID   =      9
ELEV      =  6000.00
ERROR_N   =      40
ERROR_E   =      40
POINT_ID  = 300600
X-COORD   = -106.594455556
Y-COORD   =  43.542048056
AVAIL_FLAG = Y
```

2.3.2 LABELS_GCDB.PAT

```
AREA      =      0.00000
PERIMETER =      0.00000
LABELS_GCDB# =      2
LABELS_GCDB-ID =      2
SEC_NO    = 001
SEC_FRAC  =
SEC_DUP   =
NOMINAL_LOCATION = D
QUARTER   = NE
SURVEY_TYPE = A
SURVEY_NUMBER =
SURVEY_SUFFIX =
SURVEY_NOTE =
ACREAGE   = 40.000
CONFLICT_CD =
PRINMER_CD = 06
TIER_NO   = 041
TIER_FRAC = 0
TIER_DIR_CD = N
RANGE_NO  = 081
RANGE_FRAC = 0
RANGE_DIR_CD = W
TOWNSHIP_DUP_CD =
LATITUDE = 43.551183306
LONGITUDE = 106.518346750
```

GCDB Coverage Format Description Document



2.3.3 GCDB.NAT

```
ARC#          =  1
GCDB#         =  2
GCDB-ID       =  2
ELEV          = 6000.00
ERROR_N        = 214
ERROR_E        = 455
LINE_CNT       = 24
LINE_TYPE      = 3
LINE_PEN       = 4
LX_SEC         = 0
POINT_ID       = 660700
X-UTM-ST       = 377159.88
Y-UTM-ST       = 4823531.82
X-COORD        = -106.520832806
Y-COORD        = 43.556570000
SYM_VALUE      = 122
```

2.3.4 GCDB.AAT

```
FNODE#        =  4
TNODE#        =  3
LPOLY#        =  1
RPOLY#        =  4
LENGTH         =     0.00498
GCDB#         =  3
GCDB-ID       = 1456
TYPE          =  0
SYMBOL         = 11
ORIG_ARC      = 1456
DANGLE_FLAG    = 0
```

2.3.5 GCDB.AAT (with cogo attributes for curves)

```
FNODE#        = 577
TNODE#        = 572
LPOLY#        =  0
RPOLY#        =  0
LENGTH         =    37.37700
GCDB#         = 1149
GCDB-ID       = 1149
ANGLE          = N17-22-20E
DISTANCE       = 35.50
RADIUS         = 33.61
DELTA          = 63-45-12
TANGENT        = 20.90
ARCLENGTH     = 37.40
SIDE           = L
RADIUS2        =
TANGENT2      =
```

GCDB Coverage Format Description Document



TYPE = 0
SYMBOL = 14
ORIG_ARC = 0
DANGLE_FLAG =

2.3.6 GCDB.PAT

AREA = 0.00002
PERIMETER = 0.01713
GCDB# = 2
GCDB-ID = 525
SEC_NO = 001
SEC_FRAC =
SEC_DUP =
NOMINAL_LOCATION = A
QUARTER =
SURVEY_TYPE = L
SURVEY_NUMBER = 1
SURVEY_SUFFIX =
SURVEY_NOTE =
ACREAGE = 40.000
CONFLICT_CD =
PRINMER_CD = 06
TIER_NO = 041
TIER_FRAC = 0
TIER_DIR_CD = N
RANGE_NO = 081
RANGE_FRAC = ORANGE_DIR_CD = W
TOWNSHIP_DUP_CD =
LATITUDE = 43.554781111
LONGITUDE = 106.518345028

2.3.7 GCDB.PATTWP

AREA = 0.01008
PERIMETER = 0.43709
TWP# = 2
TWP-ID = 2
STATE_CD = WY
PRINMER_CD = 06
TIER_NO = 041
TIER_FRAC = 0
TIER_DIR_CD = N
RANGE_NO = 081
RANGE_FRAC = 0
RANGE_DIR_CD = W
TOWNSHIP_DUP_CD =

GCDB Coverage Format Description Document



2.3.8 GCDB.PATSECT

AREA	=	0.00027
PERIMETER	=	0.07174
SECT#	=	6
SECT-ID	=	6
SECTION	=	003
SEC_FRAC	=	
SEC_DUP	=	

2.3.9 GCDB.PATQTR

AREA	=	0.00212
PERIMETER	=	1.12177
QTR#	=	2
QTR-ID	=	2
QUARTER	=	NW

GCDB Coverage Format Description Document



3.0 Translation to the Cadastral Data Transfer Profile for the National Spatial Data Infrastructure

3.0.1 CONTROL POINT ATTRIBUTES (ctrl.pat)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
CTRL#	N/A	N/A
CTRL-ID	N/A	N/A
ELEV	TWN.COORDS	ELEV
ERROR_N	TWN.COORDS	YACC *
ERROR_E	TWN.COORDS	XACC *
POINT_ID	TWN.LACORN	CORNNO **
X-COORD	TWN.COORDS	EAST
Y-COORD	TWN.COORDS	NORTH
AVAIL_FLAG	N/A	N/A

* Different methods may be used to define reliability. GMM records the error in feet for each location, while PCCS records an average reliability.

** GCDB Coverage Format utilizes a 6 character point-id value. NSDI uses a three-character corner number.

GCDB Coverage Format Description Document



3.0.2 LABEL ATTRIBUTES (labels_gcdb.pat)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
LABELS_GCDB#	N/A	N/A
LABELS_GCDB-ID	N/A	N/A
SEC_NO	TWN.FIRST	SECTN
SEC_FRAC	TWN.FIRST	SECTN
SEC_DUP	TWN.FIRST	FRSTSF
NOMINAL_LOCATION	N/A	N/A
QUARTER	TWN.SECOND	QSECTN
SURVEY_TYPE	TWN.SURDES	SURSYS
SURVEY_NUMBER	TWN.SURDES	SURNUM
SURVEY_SUFFIX	TWN.SURDES	SURNUM
SURVEY_NOTE	TWN.SURDES	SURNUM
ACREAGE	TWN.PARARA	PARAR
CONFLICT_CODE	N/A	N/A
PRINMER_CD	UNDEFINED	UNDEFINED
TIER_NO	TWN.TWNSHP	TOWN
TIER_FRAC	TWN.TWNSHP	TWNFRT
TIER_DIR_CD	TWN.TWNSHP	TWNDIR
RANGE_NO	TWN.TWNSHP	RANGE
RANGE_FRAC	TWN.TWNSHP	RNGFRT
RANGE_DIR_CD	TWN.TWNSHP	RNGDIR
TOWNSHIP_DUP_CD	TWN.TWNSHP	TWNDUP
LATITUDE	N/A	N/A
LONGITUDE	N/A	N/A

GCDB Coverage Format Description Document



3.0.3 NODE ATTRIBUTES (gcdb.nat)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
ARC#	N/A	N/A
GCDB#	N/A	N/A
GCDB-ID	N/A	N/A
ELEV	TWN.COORDS	ELEV
ERROR_N	TWN.COORDS	YACC *
ERROR_E	TWN.COORDS	XACC*
LINE_CNT	N/A	N/A
LINE_TYPE	N/A	N/A
LINE_PEN	N/A	N/A
LX_SEC	N/A	N/A
POINT_ID	TWN.COORDS	CORNNO **
X-UTM-ST	N/A	N/A
Y-UTM-ST	N/A	N/A
X-COORD	TWN.COORDS	EAST
Y-COORD	TWN.COORDS	NORTH
SYM_VALUE	N/A	N/A
REDEFINED ITEMS		
PREFIX	TWN.LACORN	CORNNO **
SUFFIX	TWN.LACORN	CORNNO **

* Different methods may be used to define reliability. GMM records the error in feet for each location, while PCCS records an average reliability.

** The GCDB Coverage Format utilizes a 6 character point-id value. NSDI uses a three-character corner number.

GCDB Coverage Format Description Document



3.0.4 ARC ATTRIBUTES (gcdb.aat)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
FNODE#	N/A	N/A
TNODE#	N/A	N/A
LPOLY#	N/A	N/A
RPOLY#	N/A	N/A
LENGTH	N/A	N/A
GCDB#	N/A	N/A
GCDB-ID	N/A	N/A
TYPE	N/A	N/A
SYMBOL	N/A	N/A
ORIG_ARC	N/A	N/A
DANGLE_FLAG	N/A	N/A

GCDB Coverage Format Description Document



3.0.5 ARC ATTRIBUTES (gcdb.aat - for tangent, circular and spiral curves)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
FNODE#	N/A	N/A
TNODE#	N/A	N/A
LPOLY#	N/A	N/A
RPOLY#	N/A	N/A
LENGTH	N/A	N/A
GCDB#	N/A	N/A
GCDB-ID	N/A	N/A
ANGLE	TWN.CIRCUR	CENANG
DISTANCE	TWN.CIRCUR	LNGCRD
RADIUS	TWN.CIRCUR	RAD
DELTA	TWN.OTHCUR	PARAMETERS
TANGENT	TWN.OTHCUR	PARAMETERS
ARCLENGTH	TWN.OTHCUR	PARAMETERS
SIDE	TWN.OTHCUR	PARAMETERS
RADIUS2	TWN.OTHCUR	PARAMETERS
TANGENT2	TWN.OTHCUR	PARAMETERS
TYPE	N/A	N/A
SYMBOL	N/A	N/A
ORIG_ARC	N/A	N/A
DANGLE_FLAG	N/A	N/A

GCDB Coverage Format Description Document



3.0.6 POLYGON ATTRIBUTES (gcdb.pat)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
GCDB#	N/A	N/A
GCDB-ID	N/A	N/A
SEC_NO	TWN.FIRST	SECTN
SEC_FRAC	TWN.FIRST	SECTN
SEC_DUP	TWN.FIRST	FRSTSF
NOMINAL_LOCATION	N/A	N/A
QUARTER	TWN.SECOND	QSECTN
SURVEY_TYPE	TWN.SURDES	SURSYS
SURVEY_NUMBER	TWN.SURDES	SURNUM
SURVEY_SUFFIX	TWN.SURDES	SURNUM
SURVEY_NOTE	TWN.SURDES	SURNUM
ACREAGE	TWN.PARARA	PARAR
CONFLICT_CD	N/A	N/A
PRINMER_CD	UNDEFINED	UNDEFINED
TIER_NO	TWN.TWNSHP	TOWN
TIER_FRAC	TWN.TWNSHP	TWNFRT
TIER_DIR_CD	TWN.TWNSHP	TWNDIR
RANGE_NO	TWN.TWNSHP	RANGE
RANGE_FRAC	TWN.TWNSHP	RNGFRT
RANGE_DIR_CD	TWN.TWNSHP	RNGDIR
TOWNSHIP_DUP_CD	TWN.TWNSHP	TWNDUP
LATITUDE	N/A	N/A
LONGITUDE	N/A	N/A

GCDB Coverage Format Description Document



3.0.7 REGION ATTRIBUTES

SUBCLASS TWP (gcdb.pattwp)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
TWP#	N/A	N/A
TWP-ID	N/A	N/A
SEC_NO	TWN.FIRST	SECTN
STATE_CD	TWN.LADESC	STATE
PRINMER_CD	UNDEFINED	UNDEFINED
TIER_NO	TWN.TWNSHP	TOWN
TIER_FRAC	TWN.TWNSHP	TWNFRT
TIER_DIR_CD	TWN.TWNSHP	TWNDIR
RANGE_NO	TWN.TWNSHP	RANGE
RANGE_FRAC	TWN.TWNSHP	RNGFRT
RANGE_DIR_CD	TWN.TWNSHP	RNGDIR
TOWNSHIP_DUP_CD	TWN.TWNSHP	TWNDUP
REDEFINED ITEM		
TOWNSHIP	N/A	N/A

SUBCLASS SECT (gcdb.patsect)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
SECT#	N/A	N/A
SECT-ID	N/A	N/A
SECTION	TWN.FIRST	SECTN

GCDB Coverage Format Description Document



SUBCLASS QTR (gcdb.patqtr)

ARC/INFO ITEM NAME	NSDI TABLE	NSDI ITEM NAME
AREA	N/A	N/A
PERIMETER	N/A	N/A
QTR#	N/A	N/A
QTR-ID	N/A	N/A
QUARTER	TWN.SECOND	